



COMPRESSED GAS ASSOCIATION, INC.

SAFETY ALERT

SA-11^{3/4}2000

1725 JEFFERSON DAVIS HWY., SUITE 1004
ARLINGTON, VA 22202
703-412-0900
E-MAIL: CGA@CGANET.COM

POTENTIAL FOR HIDDEN CRYOGENIC LIQUID CYLINDER CONTAMINATION

All cylinders have the potential for exposure to external contamination during their service life. External contamination can occur while in storage or in use in areas where contaminants are present in the form of air-borne mist or particulate matter. External contamination can also occur during transportation. Road-film and salts being thrown up by vehicle traffic, oil leaks from the transport vehicle, and even unburned engine fuel can result in the accumulation of contaminants. Ambient weather and local service conditions can cause wide variations in the potential for accumulation. Such contamination is of special concern where oxidizing gases are involved.

Although it is recommended that all cylinders undergo a thorough pre-fill inspection, in some cryogenic liquid cylinder designs, the area beneath the liquid level sight-glass is hidden by a protective cover. Two cryogenic oxygen cylinder fires have been reported, which may have been caused by small leaks at the base of the liquid level sight-glass, augmented by hydrocarbon contamination in the same area.

Liquid oxygen containers must be properly cleaned for oxygen service and must be kept clean and free of grease, oil, or other hydrocarbon materials, which can combine with oxygen with explosive violence. Detailed information on methods of cleaning is provided in CGA G-4.1 *Cleaning Equipment For Oxygen Service* [1].

Reference

[1] CGA G-4.1, *Cleaning Equipment For Oxygen Service*, Compressed Gas Association, Inc., 1725 Jefferson Davis Hwy., Suite 1004, Arlington, VA 22202.

PLEASE NOTE:

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document should not be confused with federal, state, provincial, or municipal specifications or regulations, insurance requirements or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding.

A catalog listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters are available at no charge upon request from the Compressed Gas Association, Inc. Phone 703-412-0900, ext. 799. Fax 703-412-0128. E-mail CustomerService@cganet.com.

SEA Council

©2000 BY THE COMPRESSED GAS ASSOCIATION, INC. ALL RIGHTS RESERVED.
1725 JEFFERSON DAVIS HIGHWAY, SUITE 1004, ARLINGTON, VA 22202

★ ★ CGA GRANTS PERMISSION TO REPRODUCE THIS SAFETY ALERT ★ ★